

SPEZIFIKATIONSTABELLE HDS-Serie DIGITALE SPIRAL-KÄLTETROCKNER

Modell	Durchflussmenge	Verbindung	El. Verbindung	Stromverbrauch
	<i>m<sup>3</sup>/h</i>		<i>V/Ph/Hz</i>	<i>kW</i>
HDS 1800	1.800	DN 80	400/3/50 460/3/60	2,9
HDS 2250	2,250	DN 100		3,9
HDS 2700	2,700	DN 100		5,6
HDS 3150	3,150	DN 150		6,2
HDS 3600	3.600	DN 150		6,9
HDS 4500	4,500	DN 150		8,9
HDS 5400	5,400	DN 150		10,3
HDS 6300	6,300	DN 200		400/3/50 460/3/60
HDS 7200	7,200	DN 200	13,8	
HDS 9000	9.000	DN 200	17,8	
HDS 10800	10,800	DN 200	20,6	

ABMESSUNGSTABELLE HDS-Serie DIGITALE SPIRAL-KÄLTETROCKNER

Modell	Abmessungen			Gewicht
	A	B	C	
	<i>mm</i>			<i>kg</i>
HDS 1800	1,232	1,033	2,162	520
HDS 2250	1,243	1,301	2,162	600
HDS 2700	1,243	1,301	2,162	665
HDS 3150	1,400	1,509	2,162	840
HDS 3600	1,400	1,509	2,162	850
HDS 4500	1,400	1,509	2,162	950
HDS 5400	1,400	1,509	2,162	950
HDS 6300	1,438	2,965	2,800	1,850
HDS 7200	1,438	2,965	2,800	1,950
HDS 9000	1,438	2,965	2,800	2,080
HDS 10800	1,438	2,965	2,800	2,080